





Product Type: Plug-in terminal-Plug

Product Name:MC-ROX7.5H08P-0002

Product Description: Pitch:7.5mm Rated Voltage : 630V Rated Current:20A Connection method : Spring cage connection colour : customizable

Product Size



Parameters

⌘ SUPU ID	MC-ROX7.5H08P-0002
⌘ Pitch	7.5
⌘ Number of connections	8
⌘ Connection method	Spring cage connection

☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn Plated/Au Plated Area
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	20A
☞ IEC Rated Voltage	630V
☞ Overvoltage category	III/III/ II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	6KV 6KV 6KV
☞ UL Rated Current	14.5A - 5A
☞ UL Rated Voltage	300V - 600V
☞ Conductor cross section rigid	0.2-2.5mm ²
☞ Conductor cross section flexible	0.2-2.5mm ²
☞ Conductor cross section flexible,with furrule	0.25-1.5mm ²
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	-
☞ Stripping length	8-9mm
☞ Use group	B/C/D

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat