



Product Type: Plug-in terminal-Socket

Product Name:MC-POX7.5H06-0002

Product Description: Pitch: 7.5mm Rated Voltage : 630V Rated Current: 20A colour : customizable

Parameters

☞ SUPU ID	MC-POX7.5H06-0002
☞ Pitch	7.5
☞ Number of connections	6
☞ Connection method	-
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn Plated/Au Plated Area
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	630V
☞ IEC Rated Voltage	20A

⌘ Overvoltage category	III III II
⌘ Degree of pollution	3 2 2
⌘ Rated impulse voltage	6.0KV 6.0KV 6.0KV
⌘ UL Rated Current	14.5A - 5A
⌘ UL Rated Voltage	300V - 600V
⌘ Conductor cross section rigid	-
⌘ Conductor cross section flexible	-
⌘ Conductor cross section flexible,with furrule	-
⌘ Locking screw Specification	-
⌘ Locking screw torque	-
⌘ Fixed Screw Specification	-
⌘ Stripping length	-
⌘ Use group	B/C/D

Commercial data

⌘ Order No	MC-POX7.5H06-0002
------------	-------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-03-16 04:05

The right to modify data belongs to SUPU.