





Product Type: Push-in spring terminal

Product Name: TP2.5-2-2-GY

Product Description: Connection method: Push in connection, IEC Rated Current: 24A, IEC Rated Voltage: 500V, Number of connections: 2, Number of levels : 1

Product Size



Parameters

☞ SUPU ID	TP2.5-2-2-GY
☞ Width	5.2mm
☞ Number of levels	1
☞ Number of connections	2

☞ Connection method	直插弹簧接线
☞ Protection Level	IP20
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Ambient temperature (operation)	-40℃~105℃
☞ Ambient temperature (assembly)	-5℃~70℃
☞ Ambient temperature (storage)	-25℃~60℃
☞ Permissible humidity (storage/transport)	30%~70%

Technical data

☞ IEC Rated Current	24A
☞ IEC Rated Voltage	500V
☞ Overvoltage category	III
☞ Degree of pollution	3
☞ Rated impulse voltage	6KV
☞ UL Rated Current	20/20/5A
☞ UL Rated Voltage	300/300/600V
☞ Conductor cross section rigid	/
☞ Conductor cross section flexible	/
☞ Conductor cross section flexible,with furrule	/
☞ Stripping length	/
☞ Use group	B/C/D

Commercial data

☞ Order No

TP2.5-2-2-GY

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat