






Product Type: Screw terminal

**Product Name:335991**

Product Description: Connection method:Screw connection,IEC Rated current:25A,IEC Rated Voltage:1000V,Number of connections:2,Number of levels : 1,Rated cross section:8-1/0AWG

## Product Size



## Parameters

|                                                                                                          |        |
|----------------------------------------------------------------------------------------------------------|--------|
|  SUPU ID               | 335991 |
|  Width                 | 16mm   |
|  Number of levels      | 1      |
|  Number of connections | 2      |

|                                            |                              |
|--------------------------------------------|------------------------------|
| ☞ Connection method                        | Screw connection             |
| ☞ Protection Level                         | IP20                         |
| ☞ Insulation material                      | PA66                         |
| ☞ Insulation material group                | I                            |
| ☞ Contact material                         | Copper                       |
| ☞ Contact plating                          | Sn,Plated                    |
| ☞ Ambient temperature (operation)          | -40°C~105°C                  |
| ☞ Ambient temperature (assembly)           | -5°C~70°C                    |
| ☞ Ambient temperature (storage)            | -25°C~60°C                   |
| ☞ Permissible humidity (storage/transport) | 30%~70%                      |
| ☞ Product type                             | Terminal block of side-entry |

## Technical data

|                                                 |                      |
|-------------------------------------------------|----------------------|
| ☞ IEC Rated Current                             | 25A                  |
| ☞ IEC Rated Voltage                             | 1000V                |
| ☞ Overvoltage category                          | III                  |
| ☞ Degree of pollution                           | 3                    |
| ☞ Rated impulse voltage                         | 8kV                  |
| ☞ UL Rated Current                              | 150A                 |
| ☞ UL Rated Voltage                              | 600V                 |
| ☞ Conductor cross section rigid                 | 10-35mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 10-35mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with furrule | 10-35mm <sup>2</sup> |
| ☞ Locking screw Specification                   | M6                   |

|                             |          |
|-----------------------------|----------|
| ⌘ Locking screw torque      | 3-3.5N.m |
| ⌘ Fixed Screw Specification | /        |
| ⌘ 固定螺钉扭矩                    | /        |
| ⌘ Stripping length          | 16-17mm  |
| ⌘ Use group                 | B/C      |
| ⌘ Rated cross section       | 8-1/0AWG |
| ⌘ UL Rated Current          | 150A     |
| ⌘ UL Rated Current          | 600V     |

## Commercial data

|            |        |
|------------|--------|
| ⌘ Order No | 335991 |
|------------|--------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



---

Date:2026-03-12 17:59

The right to modify data belongs to SUPU.