


Product Type: Fixed terminal

Product Name:MC-DTP5.0A40P-BK-0001

Product Description: Pitch:5mm Rated Voltage : 320V Rated Current:17.5A Connection method : Push-in spring connection colour : customizable



## Product Size



## Parameters

|                         |                       |
|-------------------------|-----------------------|
| ⌘ SUPU ID               | MC-DTP5.0A40P-BK-0001 |
| ⌘ Pitch                 | 5                     |
| ⌘ Number of levels      | Multi-Layer           |
| ⌘ Number of connections | 40                    |

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Connection method           | Push in connection               |
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn,Plated                        |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|                                                 |                        |
|-------------------------------------------------|------------------------|
| ☞ IEC Rated Current                             | 17.5A                  |
| ☞ IEC Rated Voltage                             | 320V                   |
| ☞ Overvoltage category                          | III/III/ II            |
| ☞ Degree of pollution                           | 3 2 2                  |
| ☞ Rated impulse voltage                         | 4.0KV 4.0KV 4.0KV      |
| ☞ UL Rated Current                              | 10A - 10A              |
| ☞ UL Rated Voltage                              | 300V - 300V            |
| ☞ Conductor cross section rigid                 | 0.2-1.0mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 0.2-1.0mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with furrule | 0.2-1.0mm <sup>2</sup> |
| ☞ Locking screw Specification                   | -                      |
| ☞ Locking screw torque                          | -                      |
| ☞ Fixed Screw Specification                     | -                      |
| ☞ Stripping length                              | 9-10mm                 |

Order No

MC-DTP5.0A40P-BK-0001

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat