




Product Type: Fixed terminal


Product Name:MC-TK15H02C-0001

Product Description: Pitch:15mm Rated

Voltage : 1000V Rated Current:125A Connection

method : Screw connection colour : customizable

Product Size



Parameters

 SUPU ID	MC-TK15H02C-0001
 Pitch	17
 Number of levels	Single layer
 Number of connections	2

☞ Connection method	Screw connection
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	125A
☞ IEC Rated Voltage	1000V
☞ Overvoltage category	III/III/ II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	8.0KV 8.0KV 8.0KV
☞ UL Rated Current	115A 115A -
☞ UL Rated Voltage	600V 600V -
☞ Conductor cross section rigid	0.5-35mm ²
☞ Conductor cross section flexible	0.5-35mm ²
☞ Conductor cross section flexible,with furrule	0.5-35mm ²
☞ Locking screw Specification	M5
☞ Locking screw torque	2.0N.m
☞ Fixed Screw Specification	-
☞ Stripping length	18-19mm

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat